

SILVERSPORT

BY WELLS CARGO



ALL-ALUMINUM ENCLOSED UTILITY TRAILERS

**Wells Cargo
Engineered the
SilverSport to
Exceed Your
Performance
Expectations**



6' Wide

STANDARD FEATURES

- V-Nose Profile
- LED Exterior Lighting Tail/Clearance Lights (Made in the USA)
- Aluminum Perimeter Frame
- Fully Integrated Roof and Sidewall Design
- 24" OC Tube Floor Crossmembers
- 16" OC Tube Wall Framing
- 24" OC Tube Roof Framing
- Dexter Torflex® Torsion Axles
- Goodyear® Radial Tires on Black Aluminum Wheels
- Aluminum Fenders
- 3/4" DryMax® High-Performance Flooring
- 3/8" DryMax® High-Performance Wall Liner
- LED 12V Interior Lighting with Switch (Made in the USA)
- ABS Sidewall Vents (2)
- Innovative "Double L-Lock" Roof Design is Screwless & Seamless
- Bonded (Screwless) .030 Aluminum Exterior
- 24" Stoneguard
- Aluminum Framed Side Entry Door with Flush Lock
- Choice of Standard Ramp or Rear Double Doors
- 6-Year Limited Warranty



7' Wide



ALL-ALUMINUM ENCLOSED UTILITY TRAILERS

Model		WAUV6X121	WAUV7X1422	WAUV7X1622	WAUV85X1622*	WAUV85X2022*	WAUV85X2424
Body:	Length (Incl. "V")	13'9"	16'0"	18'0"	18'5"	22'5"	26'5"
	Width	6'0"	6'9"	6'9"	8'5"	8'5"	8'5"
Overall:	Length	16'6"	18'6"	20'6"	20'5"	24'5"	28'5"
	Width	7'9"	8'6"	8'6"	8'6"	8'6"	8'6"
	Height	8'2"	8'3"	8'3"	8'4"	8'4"	8'6"
Interior:	Length	13'7"	15'10"	17'10"	18'4"	22'4"	26'4"
	Width	5'9"	6'6"	6'6"	8'2"	8'2"	8'2"
	Height	6'6"	6'6"	6'6"	6'6"	6'6"	6'6"
Platform Height:		19"	19"	19"	20"	20"	22"
Axle:	Quantity	Single	Tandem	Tandem	Tandem	Tandem	Tandem
	Capacity	3500 lbs.	7000 lbs.	7000 lbs.	7000 lbs.	7000 lbs.	10,000 lbs.
	Type	10 ⁰ Up	10 ⁰ Up	10 ⁰ Up	10 ⁰ Up	10 ⁰ Up	10 ⁰ Up
	Suspension	Torflex®	Torflex®	Torflex®	Torflex®	Torflex®	Torflex®
	Brakes	OPT	STD	STD	STD	STD	STD
Tires:	Size	ST205/75R15	ST205/75R15	ST205/75R15	ST205/75R15	ST205/75R15	ST225/75R16
	Load Range	C	C	C	C	C	D
	Type	Goodyear® Radial	Goodyear® Radial	Goodyear® Radial	Goodyear® Radial	Goodyear® Radial	Goodyear® Radial
Wheels:		Black Aluminum	Black Aluminum	Black Aluminum	Black Aluminum	Black Aluminum	Black Aluminum
Hitch:	Ball Size	2"	2-5/16"	2-5/16"	2-5/16"	2-5/16"	2-5/16"
	To Top of Ball	16"	16"	16"	18"	18"	20"
	GVWR	2990 lbs.	7000 lbs.	7000 lbs.	7000 lbs.	7000 lbs.	10,000 lbs.
Rear Door:	Style	Ramp or Double Doors	Ramp or Double Doors	Ramp or Double Doors	Ramp or Double Doors	Ramp or Double Doors	Ramp or Double Doors
	Width x Height	64" x 74"	73" x 74"	73" x 74"	93" x 74"	93" x 74"	93" x 74"
	Hardware	Aluminum	Aluminum	Aluminum	Aluminum	Aluminum	Aluminum
Side Door:	Width	32"	32"	32"	36"	36"	36"
	Lock Style	Flush	Flush	Flush	Flush	Flush	Flush
Tube Perimeter Frame:		STD	STD	STD	STD	STD	STD
12V End Connector:		4-way	7-way	7-way	7-way	7-way	7-way
Stoneguard:		24"	24"	24"	24"	24"	24"
Sidewall Vents:		STD	STD	STD	STD	STD	STD
Interior Sidewall Liner:		3/8" DryMax	3/8" DryMax	3/8" DryMax	3/8" DryMax	3/8" DryMax	3/8" DryMax
Floor:		3/4" DryMax	3/4" DryMax	3/4" DryMax	3/4" DryMax	3/4" DryMax	3/4" DryMax

*Also available in a 10,000# GVWR.