



# SILVERSPORT

BY WELLS CARGO

## ALL-ALUMINUM RACE TRAILERS



### STANDARD FEATURES:

- Aluminum Tube Perimeter Frame
- Fully Integrated Roof and Sidewall Design
- Innovative "Double L-Lock" Aluminum Roof Design is Screwless, Seamless and virtually weathertight
- 16" DC Tube Floor Crossmembers
- 16" DC Tube Wall Framing
- 24" DC Tube Roof Framing
- Spread Axle Design with Aluminum Fenderettes
- Dexter Torflex® Torsion Axles
- Goodyear® Radial Tires on Black Aluminum Wheels
- 3/4" DryMax High-Performance Flooring
- White Vinyl Wall and Ceiling Liners with Aluminum Coves
- LED Exterior and Interior Lighting (Made in the USA)
- Bonded (Screwless) .040 Aluminum Exterior
- 24" Stoneguard
- Chrome Front Corners
- Polished Corner Casting with Chrome Center Panel
- 48" Aluminum Framed Side Entry Door with Flush Lock
- Spring-Assisted Ramp Door with Flap, 48" Beavertail
- Best-In-Class Ramp Door Opening & Width Between Wheel Wells
- Drop-Down Corner Post Jacks
- Aluminum Pull-Out Step
- 5000# D-Rings (4)
- Non-Powered Roof Vents (2)
- 6-Year Limited Warranty

[www.wellscargo.com](http://www.wellscargo.com)

 BY UNIVERSAL TRAILER

MODEL		WAR85X2422	WAR85X2424	WAR85X2824	WAR85X2825	WAR85X3234	WAR85X3235
<b>Body:</b>	<b>Length</b>	24'0"	24'0"	28'0"	28'0"	32'0"	32'0"
	<b>Width</b>	8'5"	8'5"	8'5"	8'5"	8'5"	8'5"
<b>Overall:</b>	<b>Length</b>	28'6"	28'6"	32'6"	32'6"	36'6"	36'6"
	<b>Width</b>	8'6"	8'6"	8'6"	8'6"	8'6"	8'6"
	<b>Height</b>	8'10"	8'11"	8'11"	9'0"	8'11"	9'0"
<b>Interior:</b>	<b>Length</b>	23'8"	23'8"	27'8"	27'8"	31'8"	31'8"
	<b>Width</b>	8'2"	8'2"	8'2"	8'2"	8'2"	8'2"
	<b>Height</b>	7'0"	7'0"	7'0"	7'0"	7'0"	7'0"
<b>Width Between Wheel Boxes</b>		6'8 <sup>3</sup> / <sub>4</sub> "	6'8 <sup>3</sup> / <sub>4</sub> "	6'8 <sup>3</sup> / <sub>4</sub> "	6'8 <sup>3</sup> / <sub>4</sub> "	6'8 <sup>3</sup> / <sub>4</sub> "	6'8 <sup>3</sup> / <sub>4</sub> "
<b>Platform Height</b>		20"	21"	21"	22"	21"	22"
<b>Axle:</b>	<b>Quantity</b>	Tandem	Tandem	Tandem	Tandem	Triple	Triple
	<b>Capacity (lbs.)</b>	7000	10,400	10,400	12,000	15,600	18,000
	<b>Type</b>	10 <sup>o</sup> Up	10 <sup>o</sup> Up	10 <sup>o</sup> Up	10 <sup>o</sup> Up	10 <sup>o</sup> Up	10 <sup>o</sup> Up
	<b>Suspension</b>	Torflex®	Torflex®	Torflex®	Torflex®	Torflex®	Torflex®
	<b>Electric Brakes</b>	STD	STD	STD	STD	STD	STD
<b>Tire:</b>	<b>Size</b>	ST205/75R15	ST225/75R15	ST225/75R15	ST235/85R16	ST225/75R15	ST235/85R16
	<b>Load Range</b>	C	D	D	E	D	E
	<b>Type</b>	Goodyear® Radial	Goodyear® Radial	Goodyear® Radial	Goodyear® Radial	Goodyear® Radial	Goodyear® Radial
	<b>Wheel</b>	Black Aluminum	Black Aluminum	Black Aluminum	Black Aluminum	Black Aluminum	Black Aluminum
<b>Hitch:</b>	<b>Ball Size</b>	2 <sup>5</sup> / <sub>16</sub> "	2 <sup>5</sup> / <sub>16</sub> "	2 <sup>5</sup> / <sub>16</sub> "	2 <sup>5</sup> / <sub>16</sub> "	2 <sup>5</sup> / <sub>16</sub> "	2 <sup>5</sup> / <sub>16</sub> "
	<b>To Top of Ball</b>	20"	21"	21"	22"	21"	22"
	<b>GVWR (lbs.)</b>	7000	10,000	10,000	12,000	15,000	18,000
<b>Rear Door:</b>	<b>Style</b>	Ramp with Full Length Hinge	Ramp with Full Length Hinge	Ramp with Full Length Hinge	Ramp with Full Length Hinge	Ramp or Double Doors	Ramp or Double Doors
	<b>Beavertail Length</b>	48"	48"	48"	48"	48"	48"
	<b>Width x Height</b>	97" X 83"	97" X 83"	97" X 83"	97" X 83"	97" X 83"	97" X 83"
	<b>Hardware</b>	Recessed Cam	Recessed Cam	Recessed Cam	Recessed Cam	Recessed Cam	Recessed Cam
<b>Flush Lock Side Door (Width)</b>		48"	48"	48"	48"	48"	48"
<b>Tube Main Rails</b>		2"x 6"	2"x 6"	2"x 6"	2"x 6"	2"x 6"	2"x 6"
<b>12V End Connector</b>		7-way	7-way	7-way	7-way	7-way	7-way



Custom Interiors to your specifications



Double L-Lock Aluminum Roof — Screwless and Seamless



Welded, Integrated Roof Structure



Cast Aluminum Door Hold Backs