




**WELLS  
CARGO®**



**SILVERSPORT**  
BY WELLS CARGO

# ALUMINUM ALL-SPORT TRAILERS



The Wells Cargo SilverSport All-Sport trailer provides plenty of room to transport and store all your “hot wheels.” Made for those who love to navigate the trails, bust fresh powder and shred the pavement, but want their vehicles well-cared-for on the way home. The interior features water resistant DryMax® decking and our exclusive Rhino-Fiber™ Interior Walls for long-lasting durability and easy maintenance.

*With a Wells Cargo Behind. . . You Never Look Back!*



[www.wellscargo.com](http://www.wellscargo.com)

 BY UNIVERSAL TRAILER



		WASA85X16WT2	WASA85X20WT2	WASA85X22WT2	WASA85X24WT3
Body:	Length (including "V")	22'0"	26'0"	28'0"	30'0"
	Width	8'5"	8'5"	8'5"	8'5"
Overall:	Length	24'7"	28'7"	30'7"	32'7"
	Width	8'6"	8'6"	8'6"	8'6"
	Height	8'4"	8'4"	8'4"	8'4"
Interior:	Length (including "V")	21'8"	25'8"	27'8"	29'8"
	Length (without "V")	15'10"	19'10"	21'10"	23'10"
	Width	8'1"	8'1"	8'1"	8'1"
	Height	6'6"	6'6"	6'6"	6'6"
Width Between Wheel Boxes		79 1/2"	79 1/2"	79 1/2"	79 1/2"
Platform Height:		16 1/2"	16 1/2"	16 1/2"	16 1/2"
Axle:	Quantity	Tandem	Tandem	Tandem	Tandem
	GVWR	7000 lbs.	7000 lbs.*	7000 lbs.*	10,000 lbs.**
	Type	10° Up	10° Up	10° Up	10° Up
	Suspension	Dexter Torflex®	Dexter Torflex®	Dexter Torflex®	Dexter Torflex®
	Brakes	STD	STD	STD	STD
Radial Tires:	Size	ST205/75R15	ST205/75R15	ST205/75R15	ST225/75R15
	Load Range	C	C	C	D
	Type	Radial	Radial	Radial	Radial
Hitch:	Ball Size	2 5/16"	2 5/16"	2 5/16"	2 5/16"
	To Top of Ball	19"	19"	19"	19"
Front Ramp Door (W x H):		75" x 66"	75" x 66"	75" x 66"	75" x 66"
Rear Ramp Door (W x H):		92" x 77"	92" x 77"	92" x 77"	92" x 77"
Side Entry Door (W x H):		36" x 72"	36" x 72"	36" x 72"	36" x 72"
12V End Connector:		7-way	7-way	7-way	7-way

\*Available in 10,000# GVWR.  
 \*\* Available in 12,000# GVWR.



"Double L-Lock" Aluminum Roof Design (Screwless and Seamless)



Cast Aluminum Door Hold Backs



Locking Fuel Doors on Road Side (2)

## FEATURES | BENEFITS

- All-Aluminum Hardware
- Aluminum Tube Perimeter Frame
- Fully Integrated, All Tube, Roof and Sidewall Design
  - 16" OC Tube Crossmembers
  - 16" OC Wall Posts
  - 16" OC Tube Roof Framing
- 6' V-Front with Slant Nose with Chrome Cover
- Aluminum Fenderettes
- Dexter Torflex® Torsion Axles
- Radial Tires on Silver Aluminum Wheels
- 3/4" DryMax High-Performance Flooring
- White Rhino-Fiber Interior Sidewall and Ceiling Liners (UTC Exclusive)
- LED 12V Interior Dome Lights (2) with Switch (Made in the USA)
- LED Exterior Lighting Tail/Clearance Lights (Made in the USA)
- Wide Extruded Aluminum Top/Bottom Trim for Bold Appearance
- Innovative "Double L-Lock" Aluminum Roof Design is Screwless and Seamless
- Bonded (Screwless) .030 Aluminum Exterior
- Non-Powered Roof Vents (2)
- Sidewall Vents
- 5000# D-Rings (4)
- 24" ATP Stoneguard
- 14" x 14" Access Doors (2)
- 36" Aluminum Framed Side Entry Door with Flush Lock
- 75"W Spring-Assisted Front Ramp Door
- 92"W Spring-Assisted Rear Ramp Door with Ramp Extension
- 48" Beavertail with Ramp Door Transition
- Aluminum Slide-Out Step
- 6 Year Limited Warranty

