



WELLS  
CARGO®

**SILVERSPORT**  
BY WELLS CARGO

## ALL-ALUMINUM ENCLOSED IN-LINE SNOWMOBILE TRAILERS

The Wells Fargo SilverSport In-Line Snowmobile Trailer is designed to efficiently and effectively transport your snowmobiles. Aligned in a row from front to back, the In-Line model allows for quick getaways and streamlined towing. The industry leading 7'6" body width delivers a spacious 83½" between wheel boxes.

*With a Wells Fargo Behind... You Never Look Back!*



[www.wellscargo.com](http://www.wellscargo.com)

 BY UNIVERSAL TRAILER

		WAS75X1422	WAS75X1822	WAS75X2222
Body:	Length (including "V")	20'0"	24'0"	28'0"
	Width	7'6"	7'6"	7'6"
Overall:	Length	22'7"	26'7"	30'7"
	Width	8'6"	8'6"	8'6"
	Height	7'11"	7'11"	7'11"
Interior:	Length (including "V")	19'9"	23'9"	27'9"
	Length (without "V")	13'8"	17'8"	21'8"
Width:	Wall to Wall	7'3"	7'3"	7'3"
	Between Wheel Boxes	6'11 1/2"	6'11 1/2"	6'11 1/2"
	Height	6'0"	6'0"	6'0"
	Platform Height:	20"	20"	20"
Axle:	Quantity	Tandem	Tandem	Tandem
	Capacity	7000 lbs.	7000 lbs.	7000 lbs.
	Type	10° Up	10° Up	10° Up
	Suspension	Dexter Torflex®	Dexter Torflex®	Dexter Torflex®
	Brakes	STD	STD	STD
Radial Tires:	Size	ST205/75R15	ST205/75R15	ST205/75R15
	Load Range	C	C	C
	Type	Radial	Radial	Radial
Hitch:	Ball Size	2 5/16"	2 5/16"	2 5/16"
	To Top of Ball	20"	20"	20"
GVWR:		7000 lbs.	7000 lbs.	7000 lbs.
Front Door (W x H):		73" x 60"	73" x 60"	73" x 60"
Rear Door (W x H):		82" x 68"	82" x 68"	82" x 68"
Side Door (W x H):		36" x 66"	36" x 66"	36" x 66"



"Double L-Lock" Aluminum Roof Design (Screwless and Seamless)



Cast Aluminum Door Hold Backs



Locking Fuel Doors on Road Side (2)



## FEATURES | BENEFITS

- All-Aluminum Hardware
- 2" x 6" Aluminum Tube Perimeter Frame
- Fully Integrated, All Tube, Roof and Sidewall Design
  - 24" OC Floor Crossmembers
  - 16" OC Wall Posts
  - 16" OC Roof Framing
- 6' V-Nose Front with Slope
- 72" Front Ramp Door with Ski Guide
- Black Aluminum Wheels
- 3/4" DryMax® High Performance Flooring
- 24" DryMax® Kickplate
- ABS Sidewall Vents (pr)
- Locking Fuel Doors (2)
- 5000# D-Rings with Welded Plate (6)
- LED Dome Lights with Switch (2)
- .030 Bonded (Screwless) Exterior
- Wide Extruded Aluminum Top/Bottom Trim for Bold Appearance
- Innovative "Double L-Lock" Aluminum Roof Design is Screwless and Seamless
- 36" Aluminum Framed Side Door with Flush Lock
- Spring-Assisted Rear Ramp Door with 16" Flap (3000# rated)
- Aluminum Bar Locks on Rear Door
- ATP Stoneguard
- LED Exterior Tail and Clearance Lights (Made in the USA)
- 7-Way 12V End Connector
- 6-Year Limited Warranty