

**WELLS
CARGO®**

FASTTRAC® THE ALL-PURPOSE TRAILER

VALUE-DRIVEN WITH A SPIRIT THAT'S BORN TO HAUL!

The FastTrac® brings a whole new level of value to the light-duty recreational cargo trailer market. A balanced combination of versatility and affordability, the FastTrac® delivers on all fronts. From its unpretentious styling to its uncompromising dependability, only Wells Cargo® could pack so much value into an entry-level trailer.



Trailers shown may feature optional equipment available at an additional charge.

FASTTRAC®

SPECIFICATIONS



	FT58S2	FT610S2	FT612S2	FT714T2	FT716T2
Body: Length Width	9' 5" 5' 0"	11' 7" 6' 0"	13' 7" 6' 0"	15' 7" 7' 0"	17' 7" 7' 0"
Overall: Length Width Height	11' 6" 6' 8" 7' 2"	14' 0" 7' 8" 8' 2"	16' 0" 7' 8" 8' 2"	17' 8" 8' 6" 8' 3"	19' 8" 8' 6" 8' 3"
Interior: Length Width Height	9' 1" 4' 8" 5' 6"	11' 3" 5' 8" 6' 6"	13' 3" 5' 8" 6' 6"	15' 3" 6' 8" 6' 6"	17' 3" 6' 8" 6' 6"
Platform Height	18"	18"	18"	19"	19"
Spring Suspension E-Z[®] Lube Axles: Qty Total Capacity	Single 3,500 lbs.	Single 3,500 lbs.	Single 3,500 lbs.	Tandem 7,000 lbs.	Tandem 7,000 lbs.
Brakes with Breakaway Kit	Not Available	Optional	Optional	Electric Drum	Electric Drum
Radial Tire Size Tire Load Range	ST205/75R15 C	ST205/75R15 C	ST205/75R15 C	ST205/75R15 C	ST205/75R15 C
Hitch Ball Size	2"	2"	2"	2-5/16"	2-5/16"
Hitch Height to Top of Ball	16"	16"	16"	17"	17"
Hitch Weight (% of Curb Weight)	10% to 15%	10% to 15%	10% to 15%	10% to 15%	10% to 15%
Curb Weight (Approximate)	935 lbs.	1,195 lbs.	1,325 lbs.	2,125 lbs.	2,275 lbs.
GVWR	2,990 lbs.	2,990 lbs.	2,990 lbs.	7,000 lbs.	7,000 lbs.
Payload Capacity (Approximate)	2,055 lbs.	1,795 lbs.	1,675 lbs.	4,875 lbs.	4,725 lbs.
Rear Door Opening - Width x Height	51" x 59.25"	63" x 72"	63" x 72"	63" x 72"	63" x 72"
Side Door Opening - Width x Height	N/A	32" x 72"	32" x 72"	32" x 72"	32" x 72"
12v Male Connection	4-way	4-way	4-way	7-way	7-way
Tube Main Rails	2" x 3"	2" x 3"	2" x 3"	2" x 4"	2" x 4"

STANDARD FEATURES

- Exclusive Bull Nose Profile
- 15" Radial Tires with Silver Spoke Wheels
- Smooth Jeep Fenders (*Smooth Teardrop on 7' Wide Models*)
- Ball Coupler Hitch
- Safety Chains with Clevis Hook and Latch
- White .024 Aluminum Exterior (*With Screws*)
- 1-Piece Aluminum Roof
- 12v LED Exterior Lighting & Slim Line Tail Lights
- 16" Starbright Stoneguard
- Flow-Thru Sidewall Vents
- Rear Ramp Door with Spring Assist (*Single Swing Door on 5x8 Model*)
- 32" Side Entry Door with Bar Lock (*No Side Door on 5x8 Model*)
- 12v Dome Light
- 3/4" PlexCore™ Decking
- Economy Sidewall Liner
- 500 lb. Wall Mounted Rope Rings (4)
- Spring Axles with 4" Drop
- E-Z Lube[®] Hubs
- Undercoated Chassis
- 16" OC Vertical Posts
- 24" OC Crossmembers
- 24" OC Tube Roof Bows
- 1-Year Limited Warranty

DELUXE PACKAGE UPGRADES

- .030 Aluminum Exterior
- Exterior Color Options
- 3/8" PlexCore™ Sidewall Liner
- (4) 5,000 lb. Floor D-Rings (*500 lb. Wall Rope Rings on 5'W models*)



Trailers shown may feature optional equipment available at additional cost.



www.wellscargo.com

Specifications, features, options, packages & pricing subject to change **without** notice. See your authorized Wells Cargo[®] dealer for more information.