

**WELLS
CARGO®**

FASTTRAC® THE ALL-PURPOSE TRAILER

VALUE-DRIVEN WITH A SPIRIT THAT'S BORN TO HAUL!

The FastTrac® brings a whole new level of value to the light-duty recreational cargo trailer market. A balanced combination of versatility and affordability, the FastTrac® delivers on all fronts. From its unpretentious styling to its uncompromising dependability, only Wells Cargo® could pack so much value into an entry-level trailer.



Trailers shown may feature optional equipment available at an additional charge.

FASTTRAC®

SPECIFICATIONS



	FT58S2	FT610S2	FT612S2	FT714T2	FT716T2
Body: Length	9' 5"	11' 7"	13' 7"	15' 7"	17' 7"
Width	5' 0"	6' 0"	6' 0"	7' 0"	7' 0"
Overall: Length	11' 6"	14' 0"	16' 0"	17' 8"	19' 8"
Width	6' 8"	7' 8"	7' 8"	8' 6"	8' 6"
Height	7' 2"	7' 8"	7' 8"	7' 9"	7' 9"
Interior: Length	9' 1"	11' 3"	13' 3"	15' 3"	17' 3"
Width	4' 8"	5' 8"	5' 8"	6' 8"	6' 8"
Height	5' 6"	6' 6"	6' 6"	6' 6"	6' 6"
Platform Height	18"	18"	18"	19"	19"
Spring Suspension E-Z® Lube Axles: Qty	Single	Single	Single	Tandem	Tandem
Total Capacity	3,500 lbs.	3,500 lbs.	3,500 lbs.	7,000 lbs.	7,000 lbs.
Brakes with Breakaway Kit	N/A	Opt.	Opt.	Electric Drum	Electric Drum
Radial Tire Size	ST205/75R15	ST205/75R15	ST205/75R15	ST205/75R15	ST205/75R15
Tire Load Range	C	C	C	C	C
Hitch Ball Size	2"	2"	2"	2-5/16"	2-5/16"
Hitch Height to Top of Ball	16"	16"	16"	17"	17"
Hitch Weight (% of Curb Weight)	10% to 15%	10% to 15%	10% to 15%	10% to 15%	10% to 15%
Curb Weight (Approximate)	935 lbs.	1,195 lbs.	1,325 lbs.	2,125 lbs.	2,275 lbs.
GVWR	2,980 lbs.	2,980 lbs.	2,980 lbs.	7,000 lbs.	7,000 lbs.
Payload Capacity (Approximate)	2,045 lbs.	1,785 lbs.	1,655 lbs.	4,875 lbs.	4,725 lbs.
Rear Door Opening - Width x Height	51" x 59.25"	63" x 67"	63" x 67"	75" x 67"	75" x 67"
12v Male Connection	4-way	4-way	4-way	7-way	7-way

STANDARD FEATURES

- Exclusive Bull Nose Profile
- 15" Radial Tires with Silver Spoke Wheels
- Smooth Jeep Fenders (*Smooth Teardrop on 7' Wide Models*)
- Ball Coupler Hitch
- Safety Chains with Clevis Hook and Latch
- White .024 Aluminum Exterior (*With Screws*)
- 1-Piece Aluminum Roof
- 12v LED Exterior Lighting & Slim Line Tail Lights
- 16" Starbright Stoneguard
- Flow-Thru Sidewall Vents
- Rear Ramp Door with Spring Assist (*Single Swing Door on 5x8 Model*)
- 32" Side Entry Door with Bar Lock (*No Side Door on 5x8 Model*)
- 12v Dome Light
- 3/4" PlexCore™ Decking
- 500 lb. D-Ring Tie-Downs (4)
- Economy Sidewall Liner
- Spring Axles with 4" Drop
- E-Z Lube® Hubs
- Electric Brakes with Breakaway Kit (*Tandem Axle Models Only*)
- 2" x 4" Tube Main Rails (*2" X 3" on Single Axle Models*)
- Entire Chassis Undercoated
- 16" OC Vertical Posts
- 24" OC Crossmembers
- 24" OC Tube Roof Bows
- 1-Year Limited Warranty



Trailers shown may feature optional equipment available at additional cost.



www.wellscargo.com

Specifications, features, options, packages & pricing subject to change **without** notice. See your authorized Wells Cargo® dealer for more information.