



**WELLS  
CARGO®**

# MOTORTRAC® SS ALUMINUM RACE TRAILERS

## NEVER SETTLE FOR SECOND PLACE

Racing is your passion and your race car is one of your most prized possessions. Short cuts are never an option. So why would you ever consider hauling your car to the track in anything other than the Wells Cargo® MotorTrac® SS? You haven't invested this much into your car and your passion to risk settling for second best now. Choose the best.

**The New MotorTrac® SS!**



Trailers shown may feature optional equipment available at an additional charge.

**MOTORTRAC®**  
SS

# SPECIFICATIONS



		MTSS8520T3	MTSS8524T3	MTSS8528T4	MTSS8532R4
<b>Body:</b>	<b>Length</b>	20' 0"	24' 0"	28' 0"	32' 0"
	<b>Width</b>	8' 4"	8' 4"	8' 4"	8' 4"
<b>Overall:</b>	<b>Length</b>	24' 6"	28' 6"	32' 6"	36' 6"
	<b>Width</b>	8' 6"	8' 6"	8' 6"	8' 6"
	<b>Height</b>	8' 9"	8' 9"	8' 10"	8' 10"
<b>Interior:</b>	<b>Length</b>	19' 8"	23' 8"	27' 8"	31' 8"
	<b>Width</b>	8' 2"	8' 2"	8' 2"	8' 2"
	<b>Height</b>	6' 10"	6' 10"	6' 10"	6' 10"
<b>Width Between Wheel Boxes</b>		80"	80"	80"	80"
<b>Height of Wheel Box from Floor</b>		10"	10"	11.25"	11.25"
<b>Platform Height</b>		19"	19"	20"	20"
<b>Torflex® Suspension E-Z Lube® Axles: Qty</b>		Tandem	Tandem	Tandem	Triple
<b>Electric Brakes with Breakaway Kit</b>		Electric Drum	Electric Drum	Electric Drum	Electric Drum
<b>Radial Tire Size</b>		ST225/75R15	ST225/75R15	ST235/85R16	ST235/85R16
<b>Tire Load Range</b>		E	E	E	E
<b>Hitch Ball Size</b>		2-5/16"	2-5/16"	2-5/16"	2-5/16"
<b>Hitch Height to Top of Ball</b>		21"	21"	22"	22"
<b>Hitch Weight (% of Curb Weight)</b>		10% - 15%	10% - 15%	10% - 15%	10% - 15%
<b>GVWR</b>		9,900 lbs.	9,900 lbs.	12,000 lbs.	18,000 lbs.
<b>Rear Ramp Door Opening - Width x Height</b>		96" x 83"	96" x 83"	96" x 83"	96" x 83"
<b>12v Male Connection</b>		7-way	7-way	7-way	7-way
<b>Tube Main Rails</b>		2"x 6"	2"x 6"	2"x 6"	2"x 6"
<b>Beavertail</b>		24"	48"	48"	48"

## STANDARD FEATURES

- Flat Front/Flat Roof Design
- All-Aluminum Frame Construction
- Aluminum Door Holdback
- Fully Integrated, All Tube, Roof, Sidewall and Chassis Design
  - 16" OC Floor Crossmembers
  - 16" OC Wall Posts
  - 16" OC Roof Framing
- .030 Aluminum Exterior Smooth Bonded
- Bright Polished Aluminum Cap and Stainless Steel Front Corners
- Bright Polished Aluminum Rear Corners and Header
- Wide Extruded Aluminum Top and Bottom Trim
- 1- Piece Aluminum Roof
- 24" ATP Stoneguard
- Spring-Assisted Rear Ramp Door with 96" Opening
- Heavy-Duty Recessed Ramp Door Paddle Latches
- 36" Side Entry Door with Flush Lock
- Spread Torflex® Axles with Skirting and Aluminum Fenderettes
- Goodyear® Radial Tires with Silver SpitFire™ Aluminum Wheels\*
- 12v LED Clear Lens Clearance Lights
- 12v LED Clear Lens Slim Line Tail Lights
- 12v LED Dome Lights (4) with Illuminated Interior Wall Switch (1)
- 14" x 14" Non-Powered Roof Vent (2)
- 5,000 lbs. Square D-Rings with Welded Plate (4)
- 3/4" PlexCore™ Flooring
- 3/8" PlexCore™ Sidewall Liner
- Ceiling Liner
- 3-Year Limited Warranty



Trailers shown may feature optional equipment available at additional charge.

\*Trailers equipped with 7,000 lb. axles do not have Goodyear® tires as standard equipment.



[www.wellscargo.com](http://www.wellscargo.com)

Specifications, features, options, packages & pricing subject to change without notice. See your authorized Wells Cargo dealer for more information.