

**WELLS
CARGO®**

MOTORTRAC® SS STACKER ALUMINUM STACKER TRAILERS

WHEN RACING IS MORE THAN A HOBBY

Has your part-time hobby become something more serious? Then check out the MotorTrac® SS Stacker trailers from Wells Cargo®. These trailers have been designed for the motorsports professional and serious recreational enthusiast. The MotorTrac SS Stackers are large enough to haul multiple vehicles, along with affording plenty of space to store spare parts, tools, diagnostic equipment, and more!



Trailers shown may feature optional equipment available at an additional charge.

MOTORTRAC®
SS

SPECIFICATIONS



	WARS85X2435	WARS85X2436	WARS85X2836	WARS85X3236
Body:				
Length	24' 0"	24' 0"	28' 0"	32' 0"
Width	8' 4"	8' 4"	8' 4"	8' 4"
Overall:				
Length	29' 0"	29' 0"	33' 0"	37' 0"
Width	8' 6"	8' 6"	8' 6"	8' 6"
Height	13' 5"	13' 5"	13' 5"	13' 5"
Interior:				
Length	23' 8"	23' 8"	27' 8"	31' 8"
Width	8' 0"	8' 0"	8' 0"	8' 0"
Height	11' 3"	11' 3"	11' 3"	11' 3"
Width Between Wheel Boxes	81"	81"	81"	81"
Platform Height at Beavertail	25"	25"	25"	25"
Auto Lift Length	13' 0"	13' 0"	16' 0"	16' 0"
Auto Lift Height	6' 8"	6' 8"	6' 8"	6' 8"
Torflex® Suspension EZ-Lube® Axles: Qty	Triple	Triple	Triple	Triple
Electric Brakes with Breakaway Kit	Electric Drum	Electric Drum	Electric Drum	Electric Drum
Radial Tire Size	LT235/85R16	LT235/85R16	LT235/85R16	LT235/85R16
Tire Load Range	G	G	G	G
Hitch Ball Size	2-5/16"	2-5/16"	2-5/16"	2-5/16"
Hitch Height to Top of Ball	23"	23"	23"	23"
Hitch Weight (% of Curb Weight)	10% - 15%	10% - 15%	10% - 15%	10% - 15%
GVWR	18,000 lbs.	21,000 lbs.	21,000 lbs.	21,000 lbs.
Curb Weight (Approximate)	7,600 lbs.	8,750 lbs.	9,600 lbs.	10,700 lbs.
Payload Capacity (Approximate)	10,400 lbs.	12,250 lbs.	11,400 lbs.	10,300 lbs.
Rear Ramp Door Opening - Width x Height	92" x 96"	92" x 96"	92" x 96"	92" x 96"
Side Double Door Opening - Width x Height	48" x 72"	48" x 72"	60" x 78"	60" x 78"
12v Male Connection	7-Way	7-Way	7-Way	7-Way
Tube Main Rails	2" x 8"	2" x 8"	2" x 8"	2" x 8"

STANDARD FEATURES

- Polished Aluminum Front Cap & Corners
- 1-Piece Aluminum Roof
- .040 Bonded Aluminum Exterior (No Screws)
- Spread Axles with Drop Skirting
- 24" ATP Stoneguard
- 8-Bolt 16" Radial Tires with Silver SpitFire Aluminum Wheels
- 2-5/16" Adjustable Height Coupler (25,000 lbs.)
- 12K Hydraulic Landing Gear with Manual Override
- 12v LED 9" x 7" Exterior Scene Lights (4)
- 3/4" PlexCore™ Decking with Black Coin Rubber Floor Covering
- 3/8" PlexCore™ Sidewall Liner with .030 White Aluminum Covering
- White Vinyl Ceiling Liner
- Cabinets: L-Shaped Base, Overhead and Generator Compartment
- Steel Car Hoist System with 36" Extension
- Bunk/Attic (6' 6" from Floor to Under Side of Bunk/Attic)
- 36" Aluminum Ramp Extension with Large Bumpers
- Generator Compartment with 48" x 32" Access Door
- Air Compressor Prep Package
- 120/240v 50 amp Motorbase Receptacle with Lock Connect
- 12v Main Shut Off Switch
- 12v LED 14" Surface Mount Ceiling Lights (8)
- 12v LED 6" Round Flush Mount Dome Lights (4)
- 16" OC Tube Crossmembers
- 16" OC Vertical Posts
- 16" OC Tube Roof Structure
- Marine Battery with Vented Interior Floor Mount Box
- D-Ring Tie-Downs with Welded Plates (4)



Trailers shown may feature *optional* equipment available at additional cost.



www.wellscargo.com

Specifications, features, options, packages & pricing subject to change **without** notice. See your authorized Wells Cargo® dealer for more information.