



**WELLS
CARGO®**

ROAD FORCE® V-FRONT MUSCLE TO MOVE

THE TRAILER THAT POWERS YOUR PASSION.

Designed and built by Wells Cargo®, the company that pioneered the cargo trailer industry over 65 years ago, the feature-rich Road Force® delivers a whole new level of value. From the rugged triple 16's (OC) tubular steel frame to the LED tail lights, the Road Force® is no stranger to quality. So for the price of an "ordinary" trailer, you can step up to the quality and value of the extraordinary Road Force®.



Trailer shown features optional equipment available at an additional charge.

ROAD FORCE®



SPECIFICATIONS

ROAD FORCE



	RFV58S2	RFV610S2	RFV612S2	RFV612T2	RFV712T2	RFV714T2	RFV716T2
Body: Length Width	9' 5" 5' 0"	11' 7" 6' 0"	13' 7" 6' 0"	13' 7" 6' 0"	13' 7" 7' 0"	15' 7" 7' 0"	17' 7" 7' 0"
Overall: Length Width Height	11' 6" 6' 8" 7' 2"	14' 0" 7' 8" 8' 2"	16' 0" 7' 8" 8' 2"	16' 0" 7' 8" 8' 3"	15' 8" 8' 6" 8' 3"	17' 8" 8' 6" 8' 3"	19' 8" 8' 6" 8' 3"
Interior: Length Width Height	9' 1" 4' 8" 5' 6"	11' 3" 5' 8" 6' 6"	13' 3" 5' 8" 6' 6"	13' 3" 5' 8" 6' 6"	13' 3" 6' 8" 6' 6"	15' 3" 6' 8" 6' 6"	17' 3" 6' 8" 6' 6"
Platform Height	18"	18"	18"	19"	19"	19"	19"
Spring Suspension E-Z Lube® Axles: Qty Total Capacity	Single 3,500 lbs.	Single 3,500 lbs.	Single 3,500 lbs.	Tandem 7,000 lbs.	Tandem 7,000 lbs.	Tandem 7,000 lbs.	Tandem 7,000 lbs.
Electric Brakes with Breakaway Kit	Not Available	Optional	Optional	Electric Drum	Electric Drum	Electric Drum	Electric Drum
Radial Tire Size Tire Load Range	ST205/75R15 C	ST205/75R15 C	ST205/75R15 C	ST205/75R15 C	ST205/75R15 C	ST205/75R15 C	ST205/75R15 C
Hitch Ball Size	2"	2"	2"	2-5/16"	2-5/16"	2-5/16"	2-5/16"
Hitch Height to Top of Ball	16"	16"	16"	17"	17"	17"	17"
Hitch Weight (% of Curb Weight)	10% to 15%	10% to 15%	10% to 15%	10% to 15%	10% to 15%	10% to 15%	10% to 15%
Curb Weight (Approximate)	935 lbs.	1,195 lbs.	1,325 lbs.	1,740 lbs.	1,975 lbs.	2,125 lbs.	2,275 lbs.
GVWR	2,990 lbs.	2,990 lbs.	2,990 lbs.	7,000 lbs.	7,000 lbs.	7,000 lbs.	7,000 lbs.
Payload Capacity (Approximate)	2,055 lbs.	1,795 lbs.	1,665 lbs.	5,260 lbs.	5,025 lbs.	4,875 lbs.	4,725 lbs.
Rear Door Opening - Width x Height	51" x 59"	63" x 73"	63" x 73"	63" x 73"	75" x 73"	75" x 73"	75" x 73"
Side Entry Door Opening - Width x Height	N/A	36" x 72"	36" x 72"	36" x 72"	36" x 72"	36" x 72"	36" x 72"
12v Male Connection	4-way	4-way	4-way	7-way	7-way	7-way	7-way
Tube Main Rails	2" x 3"	2" x 3"	2" x 3"	2" x 4"	2" x 4"	2" x 4"	2" x 4"

STANDARD FEATURES

- Exclusive Bull Nose Profile
- 15" Radial Tires with Silver Spoke Wheels
- ATP Jeep Fenders (ATP Teardrop on 7' Wide Models)
- .030 Aluminum Exterior Bonded (No Screws)
- 1-Piece Aluminum Roof
- 12v LED Slim Line Red Lens Tail Lights
- 12v LED PC/P2 Rated Clearance Lights
- 24" ATP Stoneguard
- Flow-Thru Sidewall Vents
- Rear Ramp Door w/ Spring Assist (Single Swing Door on 5x8 Model)
- 36" Side Entry Door with Flush Lock (No Side Door on 5x8 Model)
- 12v LED Dome Light with Wall Switch
- 3/4" PlexCore™ Decking
- 3/8" PlexCore™ Sidewall Liner
- Spring Axles with E-Z Lube® Hubs
- Entire Chassis Undercoated
- ArmorTech™ on A-Frame and Rear End Rail
- 16" OC Tube Vertical Posts
- 16" OC Crossmembers
- 16" OC Tube Roof Bows
- 3-Year Limited Warranty



Trailers shown feature *optional* equipment available at additional cost.



www.wellscargo.com

Specifications, features, options, packages & pricing subject to change **without** notice. See your authorized Wells Cargo® dealer for more information.